

### Test stand

## **MX-5000N**

# **Motorized Test Stand**

IMADA CO., LTD. 1/3



[Applications]

(Force gauge and speed/length meter are sold separately.)

#### -Various material strength test up to 5000N

- (Tensile strength, Compressive strength, Shearing strength, etc.)
- -Analysis of mechanical parts for break point.

#### [Feature]

- -Stable measuring is possible with constant speed (adjustable).
- -Continuous testing is possible by the auto-cycle function with adjustable upper and lower limits.
- -Operation efficiency is excellent by the spacious design.
- -Motion Control by force is possible by connecting with IMADA ZTS/ZTA series force gauges (Specified cable is required).
- Specified measuring speed can be maintained. The speed can be recalled according to your needs.
- Efficient measurement is possible to repeat by setting of speed change point.

2016/07/12



#### [Specifications]

| Model                | MX-5000N   |  |  |
|----------------------|--|--|--|
| Capacity             | 5000N  |  |  |
| Stroke               | 340 mm (When mounting High Capacity Model Digital Force Gauge ZTS/ZTA series)  |  |  |
| Speed                | 10 – 300 mm/min (adjustable)   |  |  |
|                      | Fixed speed dial and Adjustable speed dial are switchable.                     |  |  |
| Speed change         | The setting the point is adjustable.   |  |  |
|                      | The speed changes from high speed to specified speed at the point.             |  |  |
| Test mode            | Manual It controls the testing motion by the panel key                         |  |  |
|                      | Single It automatically performs one cycle measurement at setting speed.       |  |  |
|                      | Continuous It automatically performs continuous cycles at setting speed.       |  |  |
| Safety feature       | Upper/lower limit, Emergency button,   |  |  |
|                      | Overload prevention (when connecting with ZTS/ZTA series)                      |  |  |
| Dimensions           | Please refer the dimensions on the next page.                                  |  |  |
| Weight               | Approx.30 kg   |  |  |
| Power                | 100 – 240V AC, approx. 75W   |  |  |
| Accessory            | Grip mount(GF-2), Power cord, Tool, Instruction manual, Spare fuse, Dust cover |  |  |
| Special<br>Functions | -Force control   |  |  |
|                      | -Overload prevention.  |  |  |
|                      | Those functions are activated when MX-5000N connects ZTS/ZTA series with the   |  |  |
|                      | specified cable.*1   |  |  |

\*1 The cable is an optional item.

#### [Additional Option]

| Model         | Specification                          |
|---------------|--|
| MX-5000N-V150 | Speed range 5 – 150 mm/min             |
| MX-5000N-E    | Mount a speed meter and a length scale |


\*Some additional options are required extra price. Also, we accept custom-made orders according to your needs. Please feel free to contact us if you need.

#### [Related Products]

| High Capacity Model Digital Force Gauge   | Force Control Cable  |
|---|--|
| ZTS/ZTA-5000N   | CB-508   |
| The digital force gauge captures accurate values by<br>the high speed 2000Hz sampling rate. The<br>advanced model ZTA enables to transfer the<br>continuous data to a USB flash drive directly<br>(The sampling rate is selectable from<br>100Hz/50Hz/1Hz). | It activates the useful functions, Overload<br>prevention and Motion control by force, by<br>connecting MX-5000N and ZTS/ZTA series. |

Rev.00 / Page 2

#### [Dimensions MX-5000N]



#### [Note]

-Force gauge is not included with this test stand.

-Various optional attachments are available.

-Please do not apply the load exceeding force of capacity.

-Please avoid rapid temperature change, high humidity, the water, the dust, and the strong shock.

-It may change without a preliminary announcement for improvement etc.