

EVA MS-DIN PLUS

FEATURES AND BENEFITS

- Temperature range -20°C to +150°C (according to models).
- Fast temperature regulation by Peltier element.
- Compatible from FIRST PLUS.
- Compatible with coaxial cylinders.



CT DIN Water jacket

ACTIVITY DOMAINS

- Food Industry
- Cosmetics pharmaceuticals
- Paint / ink / coatings
- Chemical / petroleum products
- Car industry
- Teaching
- Chocolate

TEMPERATURE CONTROL DEVICES AVAILABLE

Compatible only with bayonet coupling device

Designation	Part Number	Temperature range	Type	Prog ^{c)}	Compatible device	Compatible Measuring system	Size (pxlxh) in mm	Weight
EVA MS DIN PLUS	N950000	+5°C to +65°C	Peltier	No	FIRST, RM100 ^{b)} , RM200, DSR 500	MS DIN, MS SV ^{d)} , MS ULV, MS-CHOCOLATE	610x340x650	15Kg
EVA MS DIN PLUS	N950003	-20°C to +100°C	Peltier ^{a)}	No				
EVA MS DIN PLUS	N950005	+5°C to +65°C	Peltier	Yes				
EVA MS DIN PLUS	N950007	+5°C to 80°C	Peltier	No				
EVA MS DIN PLUS	N950008	+0°C to +150°C	Peltier	No				
EVA MS DIN PLUS	N950009	+0°C to +150°C	Peltier	Yes				
EVA 100 PLUS	N950100	Room to +100°C	Electrical	No				
CT DIN	111914	-20°C to +100°C	Fluid ^{a)}	No			120x200	4kg
EVA MS DIN/MS-R PLUS	N950002	+5°C to +65°C	Peltier	No	RM100 ^{b)} , RM200, DSR 500	MS DIN, MS-R	610x340x650	15Kg
EVA MS DIN/MS-R PLUS	N950020	-20°C to +100°C	Peltier ^{a)}	Yes				
EVA MS DIN/MS-R PLUS	N950030	+0°C to +150°C	Peltier	No				
EVA MS DIN/MS-R PLUS	N950040	+0°C to +150°C	Peltier	Yes				

a) Need a chiller. Not included b) Usable with RM100 Portable and RM100 i

c) Allow temperature setting by RheoTex software or measuring head d) Need to be used with centring tool (PN 114436)