



Aquant

Protimeter Non-Invasive Moisture Meter

The Aquant is a non-invasive rapid test moisture meter for a wide range of building and construction materials.



Features

- Measures up to 3/4" (19 mm) below the surface
- Adjustable auto off
- Audible tone
- Hold feature
- Backlit LCD display
- Color arc LED display

Benefits

- Detects moisture directly in materials and below wall and floor coverings such as tile, wood and vinyl
- Not adversely affected by surface moisture such as condensation
- Dual display LCD and LED for easy reading
- Color changing LEDs to show moisture condition green (dry), yellow (at risk) and red (wet)

Amphenol
Advanced Sensors

NEURTEK
i n s t r u m e n t s

Aquant Specifications

Dimensions (h x w x d)

7 in x 1.9 in x 2 in (175 mm x 48 mm x 50 mm)

Display 1

Digital LCD

Display 2

60 LEDs green (dry), yellow (at risk) and red (wet)

Measurement Range

Non-invasive (RF) 70 to 999 (relative)

Dry (green) — 70-169

At Risk (yellow) — 170 - 199

Wet (red) — 200-999

Depth of Moisture

Up to 3/4 in (19 mm)

Case

Pouch with belt loop

Power

9 V (supplied)

Gross Weight

4 oz (100 g)

Warranty

2 years on mechanical or manufacturing defects.
Does not include wearing part or accessories.

Part Number

BLD5765



quality control instruments

T.+34 943 82 00 82 · info@neurtek.com

www.neurtek.com

Amphenol
Advanced Sensors

www.amphenol-sensors.com

© 2014 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.
Other company names and product names used in this document are the registered trademarks or
trademarks of their respective owners.

AAS-920-079D-10/2014