



# BaleMaster

## Digital Instrument for Rapid Assessment of Moisture Levels in Straw and Hay Bales



### Applications

The Protimeter Digital BaleMaster is a hand-held instrument which displays results on a large LCD Digital Display. It is supplied with a durable 600mm (24") stainless steel probe designed to reach the center of large bales.

### Features

- Measurement range: 8.5% - 36.8%
- Strong, robust stainless steel moisture probe
- Easy to read digital display
- Colour arc LED display to show moisture condition:
  - Green (Dry)
  - Yellow (At Risk)
  - Red (Wet)
- Dual display LCD and LED for easy reading
- Audible tone



**Amphenol**  
Advanced Sensors

**NEURTEK**  
i n s t r u m e n t s

# BaleMaster Specifications

## Operating Conditions:

- Operating temperature range: 0°C to 50°C
- Humidity: 0 to 90% RH, non-condensing

## Measurement Range:

- 8.5% to 36.8%
  - Green (Dry) 8.5-15%
  - Yellow (At Risk) 15.1-19.5%
  - Red (Wet) 19.6 - 36.8%

## Power:

- 9V- Alkaline 550mAh

## Dimensions and Weight

- Size: 19cm x 6.5cm x 3.5cm (7.5" x 2.5" x 1.4")
- Gross Weight (without battery): ~228g (8oz)

## Probe Dimensions:

- Length 5584mm (23")
- Diameter 10mm (0.4")

## Buzzer:

- User adjustable audible tone indicating moisture conditions

## Regulatory Compliance:

- CE, RoHS, ETL

## Warranty:

- 2 years on mechanical or manufacturing defects. Does not include wearing parts or accessories

## Part Numbers:

- GRN6165 - Balemaster instrument and probe
- GRN6148 - Balemaster probe



instrumentos para control de calidad T.+34 943 82 00 82 ·  
info@neurtek.com www.neurtek.com

**Amphenol**  
Advanced Sensors

[www.protimeter.com](http://www.protimeter.com)  
[www.amphenol-sensors.com](http://www.amphenol-sensors.com)